

## KNX Visualisation

### Smart Control 5

for installation in walls, capacitive touch screen  
fanless, without rotating parts

### Intended use

- Visualisation and operation of system statuses and information on building automation
- For vertical installation
- Installation in flush box according to EN 60670-1
- Ensure correct orientation when installing the flush box. Mounting screws must be in vertical alignment.

### Product characteristics

- KNX visualisation in combination with Visu Pro Server (ref.-no.: JVP-SERVER-H2)
- KNX visualisation in combination with Smart Visu Server (ref.-no.: SV-SERVER-INT)
- eNet visualisation in combination with eNet server for rail mounting (ref.-no.: ENET-SERVER) with software version 2.2 or higher
- Door call function only in combination with Siedle Smart Gateway SG 650-.. or SG 150-..
- High performance HD screen
- Proximity sensor
- Graphical user interface
- Brightness level of display adapts automatically to ambient brightness
- Smart Gateway with integrated image storage

### Technical data

Rated voltage: DC 24 V SELV  
Rated capacity: < 1.5 W  
Screen diagonal: 127 mm / 5.0''  
Resolution: 720 x 1280  
Frame dimensions (W x H): 81 x 132 mm  
Power supply: PoE acc. to IEEE 802.3af  
or DC 24 V via external power supply (ref.-no. NT 2415 REG VDC, not included)  
Processor: Cortex-A53  
Loudspeaker: integrated  
Microphone: integrated  
LAN connections: 1 x 10/100 Mbit/s  
Ambient temperature: 0 ... +30 °C

Colour: black

Manufacturer: JUNG  
Ref.-no.: SC 5 SW