

# Product data sheet

## Pulse insert



### Reference number

1708 IE

### Pulse insert

for covers ref.-no.: .. 1700 .., .. 1700 P .., .. 17180 .., .. 17280 .., .. 17181 .., .. 17281 .., DWPM 17360 ..

### Intended use

- Manual or automatic control of the power unit ref-no. 1208 REG
- Operation with suitable cover of the LB Management
- Installation in flush box according to EN 60670-1

### Product characteristics

- Manual switching in combination with standard centre plate ref.-no.: .. 1700 .., .. 1700 P ..
- Automatic switching in combination with motion detectors of the LB Management
- Operation in 3- or 4-conductor circuit
- Insert designed with 2-wire technology

### Technical data

Rated voltage:	AC 230 V ~
Mains frequency:	50 Hz
Power consumption:	0.25 ... 0.45 W
Current consumption:	approx. 2.8 mA
Ambient temperature:	-5 ... +45 °C
Pulse duration:	approx. 60 ms
Pulse interval:	approx. 8 s
Connection:	screw terminals
single wire:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 2.5 mm <sup>2</sup>
stranded without ferrule:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 2.5 mm <sup>2</sup>
stranded with ferrule:	1 x 0.5 ... 4.0 mm <sup>2</sup> 2 x 0.5 ... 1.5 mm <sup>2</sup>