


Product data sheet

Standard blinds insert



Reference number

1730 JE

Standard blinds insert

without satellite input
for covers ref.-no.: .. 1700 .., .. 1701 .., .. 1750 D .., .. 1751 BT ..

Intended use

- Controlling electrically driven blinds, shutters and awnings
- Automatic time control via cover
- Operation with suitable cover of the LB Management
- Installation in flush box according to EN 60670-1

Product characteristics

- Automatic control via timer
- Test operation for functional test
- Pole changing of outputs for simplified commissioning from version V01 upwards
- Saving of a ventilation position possible using the cover

Technical data

Rated voltage:	AC 230 V ~
Mains frequency:	50/60 Hz
Ambient temperature:	-5 ... +45 °C
Contact type:	μ
Stand-by power:	max. 0.5 W
Running time:	approx. 120 s
Connected load	
Motors:	700 W
Connection	
Connection mode:	screw terminals
single wire:	1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 2.5 mm ²
stranded without ferrule:	1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 2.5 mm ²
stranded with ferrule:	1 x 0.5 ... 4.0 mm ² 2 x 0.5 ... 1.5 mm ²