

Product data sheet

Universal push-button module 4-gang



| Reference number |
|--|
| A 5094 TSM |
| KNX universal push-button module, 4-gang |
| including transparent cover ref.-no.: A 50 NA for cover kit 4-gang, ref.-no.: A 504 TSA .. can be extended by means of a push-button extension module, ref.-no.: A 509.. TSEM ETS product family: Push-button Product type: 4-gang push-button |
| Intended use |
| <ul style="list-style-type: none"> - Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc. - Installation in flush box according to EN 60670-1 |
| Product characteristics |
| <ul style="list-style-type: none"> - KNX medium: TP 256 - Push-button functions switching, dimming, controlling blinds, value transmitter, calling up light scenes etc. - One or two functions per button - To be completed with cover kit - Inscription field can be illuminated - One status LED per button, red, green or blue, adjustable - One operation LED as an orientation light and to indicate the programming status – red, green or blue adjustable - Brightness of status LED, operation LED and inscription field adjustable, can be changed during operation, e.g. during night times - Measurement of room temperature - Extension unit for room temperature controller - Disabling function: Disabling or change function mode of single or all button functions - Alarm function, optional acknowledge by pressing any button - Energy saving mode - Integrated bus coupling unit - Connection for a push-button extension module, 1-4 gang - Transparent cover kit (included) for construction site mode without design covers |
| Spare part: Transparent cover ref.-no.: A 50 NA |
| Accessories: Neutral cover ref.-no.: A 50 NA W, A 50 NA WW, A 50 NA SW, A 50 NA AL, A 50 NA CH, A 50 NA MO |