

# Product data sheet

## DALI rotary controller TW



### Reference number

1740 DSTE

### DALI rotary controller TW

#### Intended use

- Brightness setting for luminaires with DALI/DALI-2 interface
- Setting of colour temperature for luminaires with DALI Device Type 8 for tunable white acc. to IEC 62386-209
- Installation in flush box according to EN 60670-1

#### Product characteristics

- The DALI rotary controller TW takes power from the DALI voltage, which must be supplied by an external DALI power supply in accordance with IEC 62386-101.
- Saving of colour temperature limiting values
- Saving of basic brightness and switch-on brightness
- Certified acc. to IEC 62386-101 and -103 (Single Master)
- The device functions as a DALI-2 single master and should not be combined with other DALI controllers.

#### Centre plates:

AS / A ranges: ref.-no. A 1540 ..

CD range: ref.-no. CD 1540 ..

SL range: ref.-no. SL 1540 ..

LS range: ref.-no. LS 1940 .., .. 1940 ..

#### Technical data

(external DALI power supply acc. to IEC 62386-101 required)

Rated voltage DALI: DC 16 V (typ.)

Power consumption: max. 2 W

Ambient temperature: -5 ... +45 °C

Colour temperature setting: 2,000 ... 10,000 K

