


Product data sheet

Standard automatic switch 2.2 m



Reference number	
A 3281	
KNX automatic switch 2.2 m	
Standard	
for bus coupling unit 3 ref.-no.: 2073 U	
Protection level IP 44 is ensured with sealing kit ref.-no. AS A 50 DS and "IP 44 frame" of the respective design range.	
IP 44 suitable only for indoor installation	
ETS product family: Physical sensors	
Product type: Movement	
Intended use	
<ul style="list-style-type: none"> - Requirement-oriented control of lighting and other electrical loads - Mounting on bus coupling unit 3 (ref.-no.: 2073 U) 	
Product characteristics	
<ul style="list-style-type: none"> - Automatic switching of lighting depending on the thermal movement and ambient brightness - 2 PIR sensors - Detection range 180° - Integrated brightness sensor - Switch-off brightness can be set - Output functions: Switching, staircase function, switching with forced position, value transmitter, light scene extension, operating mode setting for room temperature controller - Extension of the detection area by way of operating several devices as main unit or extension unit - Sensitivity can be set manually - Status LEDs - Manual switching on the device 	
Technical data	
Colour	ivory
Range	AS range
Material:	thermoplastic
Version	Standard
Mounting height:	1.10 / 2.20 m
Thermoplastic (breakproof) high-gloss	
Colour:	ivory
Material:	thermoplastic



IP Protection level IP 44 is ensured with sealing kit ref.-no. AS A 50 DS and "IP 44 frame" of the respective design range.