

## LB Management

### Universal blinds insert

with satellite input

for covers ref.-no.: .. 1700 .., .. 1701 .., .. 1750 D .., .. 1751 BT ..

### Intended use

- Controlling electrically driven blinds, shutters and awnings
- Automatic time control via cover or satellite input
- Operation with suitable cover of the LB Management
- Installation in flush box according to EN 60670-1

### Product characteristics

- The integration into group controls or master controls is possible by means of extension inputs
- Automatic control via timer
- Test operation for functional test
- Operation as a main device or extension unit
- Wind alarm interlock via the extension input
- Pole changing of outputs for simplified commissioning from version V01 upwards
- Saving of a ventilation position possible using the cover

### Technical data

Rated voltage: AC 230 V ~

Mains frequency: 50/60 Hz

Ambient temperature: -5 ... +45 °C

Contact type:  $\mu$

Stand-by power: max. 0.2 W

Running time: approx. 120 s

Connected load

Motors: 700 W

Connection

Connection mode: screw terminals

single wire: 1 x 0.5 ... 4.0 mm<sup>2</sup>

2 x 0.5 ... 2.5 mm<sup>2</sup>

stranded without ferrule: 1 x 0.5 ... 4.0 mm<sup>2</sup>

2 x 0.5 ... 2.5 mm<sup>2</sup>

stranded with ferrule: 1 x 0.5 ... 4.0 mm<sup>2</sup>

2 x 0.5 ... 1.5 mm<sup>2</sup>

Manufacturer: JUNG

Ref.-no.: 1731 JE