

Product data sheet

Universal push-button module 3-gang



Reference number
4193 TSM
KNX universal push-button module, 3-gang
for cover kit 3-gang, ref.-no.: .. 403 TSA .. for cover 2-gang with symbols, ref.-no.: .. 402 TSAP .. for cover 4-gang with symbols, ref.-no.: .. 404 TSAP .. can be extended by means of a push-button extension module, ref.-no.: 409.. TSEM Adapter frames are included in delivery: ref.-no. LS 4 AR for LS range (pre-mounted) and ref.-no. CD 4 AR for CD range. AS / A ranges without adapter frame. Only with the ETS 3.0d version or later versions the full functionality will be available. ETS product family: Push-button Product type: 3-gang push-button 1 blue LED: operation indication 6 red LED: status indication
Intended use
- Operation of loads, e.g. light on/off, dimming, blinds up/down, brightness values, temperatures, calling up and saving light scenes, etc. - Installation in flush box according to EN 60670-1
Product characteristics
- KNX medium: TP 256 - Push-button functions switching, dimming, controlling blinds, value transmitter, calling up light scenes etc. - Measurement of room temperature - To be completed with cover kit - Two red status LEDs per button - One blue operation LED as an orientation light and to indicate the programming status - Integrated bus coupling unit - One, two or three functions per button - Push-button function or rocker function, vertical or horizontal - Connection for a push-button extension module, 1-4 gang - Transparent cover kit (included) for temporary site use without design covers