

# Product data sheet

## Temperature controller fan coil



<b>Reference number</b>	
TRD LS 9248 SW	
<b>KNX temperature controller fan coil</b>	
<b>Intended use</b>	
<ul style="list-style-type: none"> <li>- Sensor module for operating electrical fan coil units in KNX installations</li> <li>- Measurement and feedback control of the room temperature</li> <li>- Installation in flush box according to EN 60670-1</li> </ul>	
<b>Product characteristics</b>	
<ul style="list-style-type: none"> <li>- Real glass front panel</li> <li>- 8 capacitive sensor buttons</li> <li>- Internal temperature sensor</li> <li>- External temperature sensor can be evaluated</li> <li>- Control of fan coil units</li> <li>- Heating and/or cooling mode</li> <li>- Suitable for 2-pipe or 4-pipe systems</li> <li>- Up to 3 fan speeds can be controlled</li> <li>- Room temperature controller function</li> <li>- Preselection of the current energy level either through the option of 4 operating modes in accordance with KNX standard or of 5 temperature profiles for use in hotels or similar sites</li> <li>- Display for indication of actual temperature (°C or °F), fan speed, operating mode/ profile</li> <li>- 1 operating level and 2 menu levels</li> <li>- Menu levels blockable</li> <li>- 1 status LED (red/green/blue)</li> <li>- Display brightness and contrast adjustable</li> <li>- Duration of the display illumination up to 120 seconds</li> <li>- Operation as extension unit for temperature controller possible</li> <li>- Integrated bus coupling unit</li> </ul>	
<b>Technical data</b>	
KNX medium:	TP 256
Rated voltage KNX:	DC 21 ... 32 V SELV
Current consumption KNX:	8 ... 17.5 mA
Protection class:	III
Ambient temperature:	-5 ... +45 °C
Storage/transport temperature:	-20 ... +70 °C
<b>Colour:</b>	black
<b>Material:</b>	glass