

Product data sheet

LED spotlight Plug & Light



Reference number	PL S1 D05 AL SW
LED spotlight Plug & Light	
for power supply Plug & Light, ref.-no.: PL 08 U	
Intended use	
<ul style="list-style-type: none"> - Dimmable light attachment for indoor lighting - Wall or ceiling mounting by plugging onto the light socket of the Plug & Light system 	
Product characteristics	
<ul style="list-style-type: none"> - Dimming with suitable LED dimmer at constant colour temperature of 2700 K - Symmetrical optics, beam angle of 35° - Flicker-free light over the entire dimming range - Light attachment can be changed during ongoing operation - Adjustable anti-glare ring via 3 latch positions (5, 10 and 15 mm) - Swivelling by 90° - Stepless rotation through 360° 	
Technical data	
Rated voltage:	DC 12 V SELV
Power consumption:	5.6 W
Connection mode:	electrical coupling via gold-plated sliding contacts
Protection class:	III
Luminous flux:	390 lm
Colour temperature:	2,700 K
Colour rendering index:	typical 85
Beam angle:	35 °
Diameter:	42 mm
Length without anti-glare ring:	80 mm
Length with anti-glare ring:	85 ... 95 mm
Housing material:	aluminium lacquered / plastic
Energy efficiency class:	G
This luminaire contains built-in LED lamps, which cannot be replaced.	
	
Colour:	aluminium – black
Material:	thermoplastic